

Advanced AdvaPlank - Plank PVC Ceiling

n55Plus

Interlocking PVC plank system providing a flush fitting, smooth, maintenance free finish.

K13 Rigid sheet fine linings and panelling

Typical applications:

Food manufacturing areas, commercial kitchens, pharmaceutical areas, laboratories, showers, W.C's and wet hygienic areas.

Preparation

A framework of PVC battens must first be fastened to the existing ceiling or suspended from purlins at 400 – 600 mm intervals. Battens must also run around the perimeter of the ceiling area.

Advanced AdvaPlank - Plank PVC Ceiling

- Manufacturer: Advanced Hygienic Contracting Ltd.
- Web: www.cladding.co.uk
- Tel: 0330 100 0313
- Product reference: Advanced AdvaPlank - Plank PVC Ceiling

- Size (w x l):
 - [250 x 3000]
 - [250 x 4000]
 - [250 x 5000]

- Thickness: [10 mm] Manufacturer's standard

Fire rating to BS 476-7:1971:

Class1

Colour:

White.

Method of fixing:

12–14 mm stainless steel staples; direct fixed to anti corrosive grid system at regular centres as close as possible to walls. If ceiling installed with a wall lining then a sealed joint will be made at the perimeter junction.

Components:

PVC Plank, Batten, Edge trim, Division Bar, Outside Corner, Inside corner.



Advanced Hygienic Contracting reserve the right to change any product specification, design or description without prior notice. No responsibility or liability can be accepted for any loss or damage arising from any error or omission contained in this document.



advanced
changing the face of cladding

T 0330 100 0313 F 0330 100 0314 advanced@cladding.co.uk www.cladding.co.uk
Advanced Hygienic Contracting Ltd, Unit A1, Greengate, Cardale Park, Harrogate HG3 1GY

Registered in England No. 3046845 VAT No. 664810624